Product environnemental profile

Fuse NH3 500V GG

PRODUCT DESCRIPTION

Type “gG” NH fuse-links are full range breaking capacity fuse-links and are used to protect cables and equipment. They can interrupt any current surge, from the lowest fusing current up to their breaking capacity, and so can be used alone as protection. They also protect electrical devices and industrial set-ups from the electrodynamic effects of very high short-circuit currents.

The rated voltage is 500V AC and the breaking capacity is 120 kA.

These fuses comply with IEC 60269-1 and 2 standard and with VDE 0636-part 201 standard

MERSEN, France S.B
15 rue Jacques de Vaucanson
69720 Saint Bonnet de Mure,
FRANCE
T +33(0)4 72 22 66 11

PRODUCT REFERENCE

The product selected as reference is the highest rating of the range. It is the one using the most of raw materials.

Designation: Fuse NH3 500A 500V GG
Reference: M217223
Mass: 1050g (with packaging)



Functional unit: Protect equipment downstream of the circuit from the effects of an overload or a short circuit by interrupting the fault current for a reference lifetime of 20 years.

Fuses are into the "other electrical equipment, passive product" category of PSR-0005. This scenario corresponds to use at 30% of rated current for a total operating time of 30% of its lifetime.

Fuse NH3 500V GG

PRODUCT RANGE

NH3			
Reference	**Designation**	**Reference**	**Designation**
R1069078	NH3 63 A 500V GG	L213151	NH3 315 A 500V GG
S1069079	NH3 80 A 500V GG	K214162	NH3 355 A 500V GG
S235168	NH3 100 A 500V GG	T215182	NH3 400 A 500V GG
T235169	NH3 125 A 500V GG	B216201	NH3 425 A 500V GG
V235170	NH3 160 A 500V GG	Z216705	NH3 450 A 500V GG
W235171	NH3 200 A 500V GG	M217223	NH3 500 A 500V GG
V233744	NH3 224 A 500V GG	S217734	NH3 630 A 500V GG
C211602	NH3 250 A 500V GG	V228523	NH3 800 A 500V GG
A212635	NH3 300 A 500V GG		

BILL OF MATERIALS

Metals			Others		
Designation	**Mass (g)**	**%**	**Designation**	**Mass (g)**	**%**
Brass	172,25	16,95%	Ceramic	490,56	48,27%
Aluminium	72,30	7,11%	Sand	205,83	20,25%
Steel	20,64	2,03%	Cardboard	37,22	3,66%
Copper	9,40	< 0,1%	Felted cardboard	6,14	< 0,1%
Tin	5,72E-01	< 0,1%	Paper	7,80E-01	< 0,1%
Lead	3,45E-01	< 0,1%	PA 66 GF30	1,00E-01	< 0,1%
Copper Nickel alloy	3,60E-02	< 0,1%	Ink	1,90E-02	< 0,1%
Silver	2,40E-02	< 0,1%			
TOTAL	**275,55**	**27,12%**	**TOTAL**	**740,65**	**72,88%**

LYFE CYCLE

The Life Cycle Analysis is realized in compliance with ISO 14 040 and 14 044 standards and with the EIME© v5.9.3 software with the database version CODDE-2022-01.

The analysis of this product and its range represents a Hungarian manufacture and a European use.

MANUFATURING

These products are manufactured in the factory located in Hungary. This is an assembly process with no major impact on the environment. For the electrical consumption of this assembly process, the local energy mix has been used.

In addition, the Hungarian manufacturing site is ISO 14001 certified.

DISTRIBUTION

The market for these fuses is in Europe. The transport is done by road.

INSTALLATION

The fuse is mounted by hand with no power or additional equipment. All energy mixes used for end-of-life treatment of packaging are based on European data.

USE

In normal use, a fuse consumes energy through heat dissipation. It doesn't emit noise or electromagnetic radiation and doesn't require maintenance. The energy mix used is based on European data.

Fuses are into the PSR-005 category "other electrical equipment, passive product".

This scenario corresponds to use at 30% of rated current, which is 0.07 times the power dissipation in watt, *(43 x 0.07) x 3600 = 10836 joules per hour*, for a total operating time of 30% of its lifetime (20 years), *(20 x 365) x (0.3 x 24) = 52560 hours*.

The total consumption of the reference product is 10836 x 52560=569.6 megajoules.

END OF LIFE

This product family is listed in the European Directive 2012/19/EU on Waste Electrical and Electronic Equipment (WEEE). The products must be reprocessed in compliance with the legislation of the country. All energy mixes used are based on European data.

ENVIRONMENTAL IMPACTS

Environmental impact indicators

Lifecycle phase / Environmental indicators	1. Manufacturing	2. Distribution	3. Installation	4. Use	5. End of life	Total	Module D	Unit
Resource use, minerals and metals (PEF-ADPe)	3,88E-04	4,84E-11	2,00E-09	4,70E-06	2,23E-07	3,93E-04	-1,64E-05	kg SB eq.
	98,75%	0*	0*	1,20%	0,06%			
Resource use, fossils (PEF-ADPf)	7,12E+01	6,83E+00	6,22E-01	1,65E+03	4,36E+00	1,73E+03	-8,40E+00	MJ
	4,10%	0,39%	0,04%	95,22%	0,25%			
Acidification (PEF-AP)	5,08E-02	2,44E-03	2,37E-04	3,70E-01	6,17E-03	4,30E-01	-9,48E-03	mol H+ eq.
	11,82%	0,57%	0,06%	86,12%	1,44%			
Ecotoxicity, freshwater (PEF-CTUe)	2,07E+02	2,31E+00	4,47E-01	6,98E+02	1,50E+02	1,06E+03	-4,06E+01	CTUe
	19,54%	0,22%	0,04%	66,03%	14,17%			
Human toxicity, cancer (PEF-CTUh-c)	2,70E-06	7,94E-12	2,20E-08	7,56E-09	5,00E-10	2,73E-06	-1,23E-09	CTUh
	98,90%	0*	0,80%	0,28%	0,02%			
Human toxicity, non-cancer (PEF-CTUh-nc)	6,93E-07	1,49E-09	3,28E-10	3,00E-07	4,70E-08	1,04E-06	-6,94E-08	CTUh
	66,50%	0,14%	0,03%	28,80%	4,52%			
Eutrophication, freshwater (PEF-Epf)	1,94E-04	6,59E-08	4,45E-07	1,78E-04	1,57E-05	3,87E-04	-5,48E-04	kg P eq.
	50,00%	0,02%	0,11%	45,83%	4,05%			
Eutrophication marine (PEF-Epm)	4,39E-03	1,12E-03	6,25E-05	4,20E-02	4,08E-03	5,17E-02	-7,94E-04	kg N eq.
	8,49%	2,17%	0,12%	81,33%	7,89%			
Eutrophication, terrestrial (PEF-Ept)	4,78E-02	1,22E-02	4,51E-04	6,32E-01	3,47E-03	6,96E-01	-9,12E-03	mol N eq.
	6,88%	1,75%	0,06%	90,81%	0,50%			
Climate change (PEF-GWP)	4,74E+00	5,63E-01	6,14E-02	6,48E+01	2,88E-01	7,05E+01	-7,77E-01	kg CO2 eq.
	6,72%	0,80%	0,09%	91,99%	0,41%			
Climate change-Biogenic (PEF-GWPb)	5,67E-01	0,00E+00	2,74E-03	8,65E-02	1,63E-02	6,73E-01	-8,18E-02	kg CO2 eq.
	84,31%	0,00%	0,41%	12,86%	2,43%			
Climate change-Fossil (PEF-GWPf)	4,17E+00	5,63E-01	5,87E-02	6,48E+01	2,72E-01	6,98E+01	-6,95E-01	kg CO2 eq.
	5,97%	0,81%	0,08%	92,75%	0,39%			
Climate change-Land use and land use change (PEF-GWPlu)	1,86E-06	0,00E+00	0,00E+00	0,00E+00	0,00E+00	1,86E-06	0,00E+00	kg CO2 eq.
	100,00%	0,00%	0,00%	0,00%	0,00%			
Ionising radiation, human health (PEF-IR)	4,56E+02	1,25E-03	2,88E-03	9,64E+01	3,32E-02	5,52E+02	-3,41E+01	kg U235 eq.
	82,54%	0*	0*	17,45%	0*			
Land use (PEF-LU)	9,58E-01	0,00E+00	0,00E+00	1,29E+00	1,47E+00	3,71E+00	-1,97E+00	no dimension
	25,79%	0,00%	0,00%	34,73%	39,47%			
Ozone depletion (PEF-ODP)	1,07E-06	4,96E-07	4,08E-09	2,77E-07	3,26E-08	1,88E-06	-2,63E-08	kg CFC-11 eq.
	56,98%	26,36%	0,22%	14,72%	1,73%			
EF-particulate Matter (PEF-PM)	3,35E-07	6,64E-09	1,56E-09	2,87E-06	1,93E-08	3,23E-06	-5,42E-08	disease occurrence
	10,36%	0,21%	0,05%	88,79%	0,60%			
Photochemical ozone formation - human health (PEF-POCP)	1,64E-02	3,99E-03	1,21E-04	1,35E-01	1,21E-03	1,57E-01	-2,70E-03	kg NMVOC eq.
	10,48%	2,55%	0,08%	86,13%	0,77%			
Water use (PEF-WU)	1,47E+01	2,85E-02	2,66E-02	2,16E+00	8,74E+01	1,04E+02	-3,30E+02	m3 eq.
	14,10%	0,03%	0,03%	2,07%	83,78%			

0 (*) represent less than 0,01% of the total lifecycle reference flow

Fuse NH3 500V GG

Resources use indicators

Ressources use \ Lifecycle phase	1. Manufacturing	2. Distribution	3. Installation	4. Use	5. End of life	Total	Module D	Unit
Total Primary Energy	8,44E+01	6,83E+00	6,68E-01	1,97E+03	4,81E+00	2,07E+03	-1,27E+01	MJ
	4,09%	0,33%	0,03%	95,32%	0,23%			
Use of renewable primary energy excluding renewable primary energy used as raw material	1,22E+01	4,58E-05	4,59E-02	3,17E+02	4,53E-01	3,30E+02	-4,02E+00	MJ
	3,71%	0*	0,01%	96,14%	0,14%			
Use of renewable primary energy resources used as raw material	1,03E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	1,03E+00	-2,71E-01	MJ
	100,00%	0,00%	0,00%	0,00%	0,00%			
Total use of renewable primary energy resources	1,33E+01	4,58E-05	4,59E-02	3,17E+02	4,53E-01	3,31E+02	-4,29E+00	MJ
	4,01%	0*	0,01%	95,84%	0,14%			
Use of non renewable primary energy excluding non renewable primary energy used as raw material	7,12E+01	6,83E+00	6,22E-01	1,65E+03	4,36E+00	1,73E+03	-8,40E+00	MJ
	4,10%	0,39%	0,04%	95,22%	0,25%			
Use of non renewable primary energy resources used as raw material	9,64E-03	0,00E+00	0,00E+00	0,00E+00	0,00E+00	9,64E-03	0,00E+00	MJ
	100,00%	0,00%	0,00%	0,00%	0,00%			
Total use of non-renewable primary energy resources	7,12E+01	6,83E+00	6,22E-01	1,65E+03	4,36E+00	1,73E+03	-8,40E+00	MJ
	4,10%	0,39%	0,04%	95,22%	0,25%			
Use of secondary material	5,40E-06	0,00E+00	0,00E+00	0,00E+00	0,00E+00	5,40E-06	0,00E+00	MJ
	100,00%	0,00%	0,00%	0,00%	0,00%			
Use of renewable secondary fuels	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MJ
	0,00%	0,00%	0,00%	0,00%	0,00%			
Use of non renewable secondary fuels	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MJ
	0,00%	0,00%	0,00%	0,00%	0,00%			
Net use of freshwater	3,35E-01	6,65E-04	3,09E-04	5,31E-02	1,63E-01	5,52E-01	-7,96E+00	m3
	60,75%	0,12%	0,06%	9,61%	29,46%			
Biogenic carbon content in the product	1,72E-03	0,00E+00	0,00E+00	0,00E+00	0,00E+00	1,72E-03	0,00E+00	kg of C
	100,00%	0,00%	0,00%	0,00%	0,00%			
Biogenic carbon content in the packaging	1,07E-02	0,00E+00	0,00E+00	0,00E+00	0,00E+00	1,07E-02	0,00E+00	kg of C
	100,00%	0,00%	0,00%	0,00%	0,00%			

0 (*) represent less than 0,01% of the total lifecycle reference flow

Waste category indicators

Waste indicators \ Lifecycle phase	1. Manufacturing	2. Distribution	3. Installation	4. Use	5. End of life	Total	Module D	Unit
Hazardous waste disposed	1,74E+01	4,66E-04	7,29E-04	1,21E+00	1,59E-04	1,86E+01	0,00E+00	kg
	93,47%	0*	0*	6,53%	0*			
Non hazardous waste disposed	5,81E+00	5,73E-04	2,04E-01	9,33E+00	7,21E-01	1,61E+01	-2,45E-03	kg
	36,16%	0*	1,27%	58,07%	4,49%			
Radioactive waste disposed	3,19E-03	1,12E-04	2,68E-05	1,95E-03	3,15E-06	5,28E-03	0,00E+00	kg
	60,35%	2,12%	0,51%	36,97%	0,06%			

0 (*) represent less than 0,01% of the total lifecycle reference flow

Output flow indicators

Other indicators \ Lifecycle phase	1. Manufacturing	2. Distribution	3. Installation	4. Use	5. End of life	Total	Module D	Unit
Component for reuse	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	kg
	0,00%	0,00%	0,00%	0,00%	0,00%			
Materials for recycling	4,13E-01	0,00E+00	3,38E-02	0,00E+00	2,49E-01	6,96E-01	0,00E+00	kg
	59,35%	0,00%	4,86%	0,00%	35,79%			
Materials for energy recovery	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	kg
	0,00%	0,00%	0,00%	0,00%	0,00%			
Exported energy	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MJ
	0,00%	0,00%	0,00%	0,00%	0,00%			

0 (*) represent less than 0,01% of the total lifecycle reference flow

Extrapolation rules

- **For the manufacturing, distribution, installation, and end of life phases:**

For the fuses NH3 800A an 630A, the following coefficient must be applied:

	Extrapolation coefficient for rating 630A and 800A			
Type of indicators	**1. Manufacturing**	**2. Distribution**	**3.Installation**	**5. End of life**
Environmental impact indicators	1,46	1,00	1,00	1,58
Ressource use indicators	1,09	1,00	1,00	1,42
Waste category indicators	1,46	1,00	1,00	1,00
Output flow indicators	1,01	1,00	1,00	1,13
Biogenic carbon indicators	1,00	1,00	1,00	1,00

For the fuses NH3 450A and 425A, the impacts are covered by those of the reference product (NH 500A).

For the fuses NH2 400A and below (compact version), the following coefficient must be applied:

	Extrapolation coefficient for rating 400A and below			
Type of indicators	**1. Manufacturing**	**2. Distribution**	**3.Installation**	**5. End of life**
Environmental impact indicators	0,97	0,62	0,78	0,75
Ressource use indicators	1,00	0,62	0,78	0,72
Waste category indicators	0,73	0,62	0,78	0,60
Output flow indicators	0,97	1,00	0,78	0,69
Biogenic carbon indicators	0,78	1,00	1,00	1,00

- **For the use phase:**

The following coefficient must be applied:

Designation	Power dissipation at In (W)	Coefficient to apply
NH3 63 A 500V GG	6,8	**0,16**
NH3 80 A 500V GG	8,3	**0,19**
NH3 100 A 500V GG	10,7	**0,25**
NH3 125 A 500V GG	12,2	**0,28**
NH3 160 A 500V GG	15	**0,35**
NH3 200 A 500V GG	18,5	**0,43**
NH3 224 A 500V GG	20	**0,47**
NH3 250 A 500V GG	21,1	**0,49**
NH3 300 A 500V GG	20	**0,47**
NH3 315 A 500V GG	25	**0,58**
NH3 355 A 500V GG	32	**0,74**
NH3 400 A 500V GG	34	**0,79**
NH3 425 A 500V GG	34	**0,79**
NH3 450 A 500V GG	38	**0,88**
NH3 500 A 500V GG	43	**1,00**
NH3 630 A 500V GG	43,1	**1,00**
NH3 800 A 500V GG	53,2	**1,24**

POTENTIAL RECYCLABILITY

End of life of the product	Rate (%)
Recyclable component	**24,6%**
Incinerated components	**0,3%**
Waste	**75,1%**

This estimation has been calculated with EIME© v5.9.3 software with the Eco'DEEE methodology.

CHECKS

Registration N° : MERS-00063-V01.01-EN	**Drafting rules :** PCR-ed4-EN-2021 09 06 Supplemented by PSR-0005-ed2-FR-2016 03 29
Verifier accreditation N° : VH32	**Information and reference documentation :** www.pep-ecopassport.org
Date of issue : 20/10/2022	**Validity period :** 5 years
Independent verification of the declaration and data, in compliance with ISO 14025 : 2010 ☐ internal ☒ external	
The PCR review was conducted by a panel of experts chaired by Julie ORGELET (DDemain)	
PEP are compliant with XP C08-100-1 :2016 or EN 50693 :2019 The elements of the present PEP cannot be compared with elements from another program.	
Document in compliance with ISO 14025 : 2010 « Environmental labels and declarations. Déclarations environnementales de Type III"	